(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 21 July 2005 (21.07.2005)

PCT

(10) International Publication Number WO 2005/067086 A2

(51) International Patent Classification7: H01M 8/02, 8/24

(21) International Application Number:

PCT/IB2004/004237

(22) International Filing Date:

22 December 2004 (22.12.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003-427382

24 December 2003 (24.12.2003) JF

(71) Applicant (for all designated States except US): TOY-OTA JIDOSHA KABUSHIKI KAISHA [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi-ken 471-8571 (JP).

(72) Inventor; and

(75) Inventor/Applicant (for US only): INAGAKI, Toshiyuki [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyotacho, Toyota-shi, Aichi-ken 471-8571 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

 without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FUEL CELL STACK STRUCTURE



(57) Abstract: (1) In a fuel cell stack structure wherein a stack is formed by stacking cells each of which is formed by sandwiching an MEA between two separators, an adhesive layer 33a is provided between the two separators sandwiching the MEA, without a constant thickness structure or pseudo constant thickness structure provided between the separators. (2) An adhesive layer 33b is provided between adjacent cells, without a bead gasket provided therebetween. (3) The adhesive layers 33a, 33b have a Young's modulus of 100 MPa or less.

2005/067086 A2 |||||||||||||||